

TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No: MERB00005XN **Revision No:** 1

This Certificate is issued by DNV UK Limited based on authorisation of the Maritime & Coast Guard Agency (MCA) as an UK Approved Body to undertake conformity assessments on marine equipment in accordance with the requirements of the Merchant Shipping (Marine Equipment) Regulations 2016 as amended.

This is to certify:

That the Rocket parachute flares (pyrotechnics)

with type designation(s) JHR-4

Issued to Huahai Marine Signals Manufacturing Co., Ltd. Haimen. China

is found to comply with the requirements in the following Regulations/Standards: Regulation MSN 1874 Amendment 10, item No. UK/1.8. SOLAS 74 as amended, Regulation III/4, III/6, III/34 & X/3, LSA Code, 2000 HSC Code 8 and IMO MSC.1/Circ.1629

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until 2030-01-16.

Issued at London on 2025-02-13

DNV local unit: Nantong

Approval Engineer: Helge Bjørnarå



Approved Body No.: 0097

for DNV UK Ltd.

Mydlak-Röder, Christine **MER Service Responsible**

ž0Š Maritime & Coastguard Agency

by the MCA

During the period of validity of this certificate the applicable regulations (international conventions and the relevant resolutions and circulars of the IMO) and testing standards may change, therefore the product conformity may need to be re-assessed by the

Approved Body. "The Mark of Conformity" may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-control phase module (D, E or F) of Schedule 2 of the Merchant Shipping (Marine Equipment) UK Approved Body Authorised Regulations 2016, as amended is fully complied with and controlled by a written inspection agreement with an approved body. In case limitations of use apply, these should be indicated in the Annex.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Form code: MER 201.GBR

This certificate will not be valid if the manufacturer makes any changes or modifications to the approved type of equipment, which have not been notified to, and agreed with the approved body named on this certificate.



Job Id: Certificate No: MERB00005XN Revision No: 1

Product description

"JHR-4",

is a rocket parachute flare, which when fired vertically reaches an altitude of not less than 300 m. At or near the top of its trajectory, the rocket is ejecting a bright red flare with a burning time of not less than 40 seconds and with an average luminous intensity of minimum 30.000 candela.

Application/Limitation

Approved for use as Rocket Parachute Flares (pyrotechnics).

Acceptable lifetime: Expiration date not to exceed 48 months after month of manufacture.

The design assessment is based on IMO Res. MSC.48(66) as amended by IMO Res. MSC.207(81) and IMO Res. MSC.218(82).

Production and installation testing shall be carried out according to IMO Res. MSC.81(70), Part 2, Ch.4 and in compliance with ISO 15736:2006 A.2.4.

Each product is to be supplied with its manual for installation, use and maintenance.

Type Examination documentation

Test report No. 2013054 dated 2 August 2013 from Wuhan Testing Center of Marine LSA, Wuhan, Hubei, China.

Drawing No. JHR-4-00 – JHR-4-20 dated 24 April 2013 from manufacturer.

Tests carried out

Tests are documented in accordance with recommendation on testing of Life-Saving Appliances, IMO Res. MSC.81(70), Part 1, including IMO Res. MSC.200(80), IMO Res. MSC.226(82) and IMO Res. MSC.323(89).

Marking of product

The product is to be marked in accordance with ISO 15736:2006 4.3, LSA code 1.2.2.9 and 1.2.3 and the UK Mark of Conformity (see first page).

The product should be provided with brief instructions or diagrams clearly illustrating the use printed on the casing.