


EN3 POWDER TYPE FIRE EXTINGUISHER



- ◆ EN3 approved
- ◆ Ideal for industrial, commercial and domestic environment
- ◆ Colour coded for instant recognition
- ◆ All units tested by electronic leak detection



TECHNICAL SPECIFICATION								
Code No.	*FEX108	*FEX104	*FEX105	*FEX106	*FEX107	FEX109	FEX110	FEX115
Propellant	Store Pressure Type (Nitrogen Propellant)					CO ₂ Cartridge		
Extinguisher Type	1 kg	2 kg	4 kg	6 kg	9 kg	6 kg	9 kg	12 kg
Fire Rating	8A 34B	13A 89B	21A 113B	34A 233B	34A 233B	34A 233B	43A 233B	55A 233B
Operating Temperature	-20°C to 60°C							
Operating Pressure	12 bar	14 bar						
Overall Height	335 mm	400 mm	490 mm	490 mm	555 mm	490 mm	570 mm	605 mm
Full Weight	2 kg	3.3 kg	7.1 kg	9.1 kg	12.8 kg	10.5 kg	14.2 kg	19 kg
Test Pressure	25 bar							
Discharge Time (min.)	6 secs	9 secs	12 secs	15 secs	15 secs	15 secs	15 secs	15 secs
Discharge Range (approx)	4-5 m	4-5 m	5-6 m	5-6 m	5-6 m	5-6 m	5-6 m	5-6 m
Carton Size	105 x 120 x 345 mm	125 x 160 x 430 mm	180 x 200 x 495 mm	180 x 200 x 495 mm	200 x 200 x 565 mm	180 x 210 x 495 mm	200 x 200 x 565 mm	200 x 200 x 645 mm