

# MARINE AUTOMATIC IDENTIFICATION SYSTEM



## Product Description

The L-3 PROTEC™-M Marine Automatic Identification System (AIS-M) is a collision avoidance and vessel tracking tool designed to improve the situational awareness of the command and control team, while facilitating secure AIS communication between military assets. With an integrated Minimum Keyboard Display (MKD), the L-3 PROTEC-M Marine AIS offers a compact solution, which is highly desirable in the space-constrained world of bridge electronics.



## FEATURES

- Position and identification information for AIS-equipped vessels
- Ability to display AIS targets on ECDIS/ECS/ARPA with detailed navigation information
- Supports text messaging between vessels and VTS
- Smallest AIS package offering in the industry
- Non-proprietary encryption method for secure position reporting
- IMO compliant to 61993-2
- Transmit power ranges 1 to 12.5W
- STEDS protocol



# MARINE AUTOMATIC IDENTIFICATION SYSTEM



## SPECIFICATIONS

### PHYSICAL DIMENSIONS

Height	8.33 cm (3.28 in.)
Width	16.23 cm (6.39 in.)
Depth	18.36 cm (7.23 in.)
Weight	2.54 kg (5.6 lb.)

### POWER REQUIREMENTS

Input	12 to 24 VDC
Watts	16 W average, 64 W peak

### DATA I/O

Pilot Port	(1) RS422 (bi-directional)
IEC Port	(2) RS422 (bi-directional) (3) RS422 (input only)

### TRANSMITTER PERFORMANCE

TX Frequency Range	156.025 to 162.025 MHz
Tuning Resolution	12.5 kHz
Modulation	GMSK/FSK
TX Power Control	1 to 12.5 W
TX Power Accuracy	±0.7 dB
TX Frequency Drift	±500 Hz
Nominal Impedance	50 Ω
Antenna Connection	Type PL259

### RECEIVER PERFORMANCE

Number of Receivers	3
RX Frequency Range	156.025 to 162.025 MHz
Tuning Resolution	12.5 kHz
Dynamic Range	≥100 dB
Co-Channel Rejection	≥10 dB
Adjacent Channel Rejection	≥72 dB
Intermodulation Rejection	≥74 dB
In-Band Blocking	≥86 dB
Noise Figure	≤5 dB

### RECEIVER PERFORMANCE (cont'd)

Nominal Impedance	50 Ω
Maximum Input	+10 dBm (no damage)
Minimum Sensitivity	≤ -107 dBm
GPS Receiver	16-channel
DSC Receiver	Fixed on channel 70

### ENVIRONMENTAL

Operating Temperature Range	-25 °C to +55 °C
Relative Humidity	0% to 95%

\*NOTE: All specifications tested @ 25 °C

### TECHNICAL STANDARDS

IEC 61993-2
IEC 61162
IEC 60945
ITU 1371-4

### REGULATORY APPROVALS

BSH/4613/05902/0406/06
USCG APR# 165.155/ECO735/4320357

### COMPANY CERTIFICATION

L-3 Henschel's Quality Management System is ISO 9001:2008 registered



### L-3 Henschel

90 Nemco Way  
Ayer, MA 01432  
Tel: 978-784-1999  
Info.Henschel@L-3com.com  
L-3com.com/Henschel

This document consists of basic marketing information that is not defined as technical data under EAR Part 772. Data contained within this document are summary in nature and subject to change any time at L-3's discretion. Call for latest revision. All brand names and product names referenced are trademarks, registered trademarks, or trade names of their respective holders.

Henschel



Mackay Marine – High Seas  
+1 281 479 1515 marinesales@mackaymarine.com  
Mackay Communications, Satellite Solutions  
+1 919 850 3100 satserv@mackaycomm.com  
Mackay Marine Canada  
+1 902 469 8480 sales.canada@mackaymarine.com  
Mackay Marine Alaska & Pacific Northwest  
+1 206 282 8080 ballard@mackaymarine.com